

INTEGRATED DISPLAY AND IDENTIFICATION SYSTEM AND METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to communications systems, and, more particularly, to such systems for contactless identification of a proximate user and for authorizing an interface with a processor via a display device.

Description of Related Art

10 Members of groups of people often have need to access a common processor via a display monitor, or perhaps via a plurality of display monitors. Authorization is typically required for such access, which is known in the art to be accomplished via the entry of a password or by swiping a card having an encoded magnetic strip attached thereto through a reader.

15 A method is described by Theimer et al. (U.S. Pat. No. 5,611,050) that includes an ability to control and register interactions of mobile users with computational resources.

 It is known to use transponder devices to identify a person or an object within a defined proximity (Thomas et al., U.S. Patent No. 5,317,318; Carroll et al., U.S. Patent No. 5,517,188; Marsh et al., U.S. Patent Nos. 5,537,105 and 5,557,280; Tyren et al., U.S. Patent No. 5,557,085; Gelnovatch et al., U.S. Patent No. H1,606; and Tokuda et al., U.S. Patent No. 5,642,103).

SUMMARY OF THE INVENTION

20 It is therefore an object of the present invention to provide a system and method for identifying a member of a group and for authorizing the member's interaction with a processor.

It is an additional object to provide such a system and method that includes a wireless identification capability.

It is a further object to provide such a system and method that includes wireless identification capability with an existing electronic device and data transfer therebetween.

5 It is another object to provide such a system that has means for connecting to a network.

It is yet an additional object to provide an integrated device for performing the identification and interaction.

It is yet a further object to provide such a device that improves ease of access to the processor while maintaining security.

10 These objects and others are attained by the present invention, a device, system, and associated methods for providing identification of a user and authorization for the user to interact with a processor. The system comprises a transponder that has an identification code programmed thereinto. The transponder in a particular embodiment comprises a standalone portable personal identification device. In an alternate embodiment the transponder comprises a component of an
15 existing electronic device that is wearable or portable by the user.

The device comprises a detector that is adapted to receive an electromagnetic signal from the transponder that is indicative of the identification code. The electromagnetic signal is within a predetermined wavelength range, such as, for example, the radio frequency range. The detector is
20 also adapted to transduce the electromagnetic signal into an electronic signal and to transmit the electronic signal to a processor.

The processor to which the signal is routed has software means resident therein for comparing the electronic signal with a set of approved user signals and for issuing an approval code. In an alternate embodiment the processor also has software resident therein and is in electronic communication with hardware means adapted to initiate a high-speed data exchange between the device and a unit within which the transponder is housed.

The system additionally comprises display means mounted to the housing integrally with the detector. The display means is connectable for electronic communication with the processor, and is adapted to receive the approval code therefrom. A receipt of the approval code permits an interaction between the user and the processor and causes a display of a communication from the processor to the user.

In a particular embodiment contemplated, each member of a group would have a personal identification device carried on his/her person during the performance of a particular activity. For example, the system may be used by waitpersons at a restaurant for obtaining access to an intranet-based processor for entering orders and processing checks. Alternatively, members of a group spending time within the predetermined area could be given one of these devices until leaving the area to permit access to an informational kiosk to permit intragroup communications. The particular application has been disclosed in the present inventor's copending patent application 09/510,758, the disclosure of which is incorporated herein by reference.

Other areas of potential application include, but are not intended to be limited to, students, faculty, and staff of a school or university; doctors, nurses, and other staff of a hospital, clinic, or doctor's or dentist's office; a laboratory conducting sensitive, classified or potentially dangerous

research; and staff of a financial institution such as a bank or investment trading facility. The invention is contemplated for use in any location wherein security and personnel identification is desired.

5 The features that characterize the invention, both as to organization and method of operation, together with further objects and advantages thereof, will be better understood from the following description used in conjunction with the accompanying drawing. It is to be expressly understood that the drawing is for the purpose of illustration and description and is not intended as a definition of the limits of the invention. These and other objects attained, and advantages offered, by the present invention will become more fully apparent as the description that now follows is read in conjunction with the accompanying drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

10 **FIG. 1** is a schematic representation of the identification and authorization system of the present invention.

15 **FIG. 2** is a schematic of the interaction between the transponder and the reader.

FIG. 3 is a block diagram of the identification system.

FIG. 4 is a schematic representation of an alternate embodiment of the system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description of the preferred embodiments of the present invention will now be presented with reference to FIGS. 1-4.

The system **10** of the present invention in a particular embodiment is intended for permitting and authorizing communication between a user carrying an identification device **50**. In a particular embodiment the identification device **50** is part of, or housed within, a personal communication and/or processing device **52** such as, but not intended to be limited to, a portable computer, a personal data recording device, a cellular telephone, a watch, or a badge. The system **10** may operate over an intranet in defined area, such as a restaurant, campus, theme park, a resort, a hotel/shopping complex, or a large business. In another embodiment the system **10** operates via an internet, which does not materially change the operation of the invention. In yet another embodiment of the invention, the system **10** operates as a unitary, standalone device.

The intranet embodiment of the system **10** (FIG. 1) includes a processor, such as a central computer **12**, networked, for example, via lines **13**, to a plurality of interaction stations **14**. Resident on the computer **12** and/or accessible thereby is a database **15** containing a list **151** of authorized user codes and, in a particular embodiment, at least one set of data **152**. Preferably a plurality of data sets **152** are present, each data set **152** accessible in correlation with a particular set of user codes. As an example, a particular group of users having a set of user codes are authorized to access a particular set of data, such as contact or scheduling information for the group. The computer **12** comprises a software package **18** installed thereon, the properties of which will be discussed in the following.

Input means affixed to each interaction station **14** are connectable for electronic communication with the computer **12** for permitting an interaction between the user and the computer **12**. The input means may comprise devices such as are known in the art, for example, a keyboard **19**.

5 A display device **20** is affixed at the interaction station **14** for access by a user and is in electronic communication with the computer **12**, here over the intranet lines **13**. The display device **20** in a preferred embodiment may comprise a video display screen, most preferably a touch screen such as are known in the art. A touch screen is adapted to transduce a physical contact therewith into a location-dependent electronic signal that may be transmitted to the computer **12**. In this
10 embodiment, therefore, the touch screen may also act as an input device. Such screens may be selected from a group consisting of a flat panel liquid crystal display and a gas plasma display, although these are not intended as limitations.

A detector adapted for communication with the identification device **50** is integrally affixed with the display device **20** at the interaction station **14**. In a preferred embodiment the
15 detector/identification device pair comprises a transponder reader **30** and transponder **50**. An exemplary interaction between these devices is illustrated schematically in FIG. 2, although this is not intended as a limitation. Here the transponder **50** comprises a memory array containing an identification code representative of the identity of the user.

20 In one embodiment the transponder **50** may be adapted to transmit a signal, such as in the radio frequency region. In a preferred embodiment, however, the transponder reader **30** comprises a transmitter/interrogator supporting a bidirectional interface through inductive coupling. When the

transponder **50** is within a predetermined range of the reader **30**, and the reader is in a "read" mode, the transponder **50** automatically transmits the contents of its memory array by modulating the contents within an incoming signal from the reader **30**. The reader **30** then detects the modulation and decodes the memory array data received. These data are then compared in the computer **12** with the database **15** of identification codes. If the incoming code matches a member of the database **15**, communication with the computer **12** is enabled.

Preferably the signal emitted by the reader **30** is within the range of 125 kHz to 13.36 MHz, in the radio frequency range. The transponder **50** may comprise a wireless or contactless, programmable or nonprogrammable, RFID transponder such as are known in the art. An exemplary schematic for the interaction between the reader **30** and the transponder **50**, including the transducing and decoding of the signal, is illustrated in FIG. 3.

The system **10** thus satisfies a need for a simplified identification of users interacting with a computer **12** to retrieve desired information pertinent to the user. In the embodiment using a touch screen **20**, when the user reaches out to interact with the screen **20**, the reader **30** automatically interrogates a transponder **50** affixed to the user and, if a match is found in the database **15**, authorizes access to the computer **12**.

Another element of the system **10** comprises means for transmitting a data set **152** from the computer **12** to the user's device **52**. In this aspect of the invention, the user code transmitted from the transponder **50** is correlated with a set of user codes **151**, and each such set **151** is in turn correlated with a data set **152** to which access is permitted. Then the data set **152** is transmitted from the database **15** via electromagnetic energy in wireless fashion to the user's device **52**, synchronizing

the data between the database 15 and the user's device 52. This data transfer preferably comprises a short-term-high-speed data interchange 51 for communicating such information as, but not intended to be limited to, area maps, a meeting place, email, a message, and/or a document. This transfer is preferably performed more quickly than would be possible using traditional wireless communications methods, with speeds in the 1 Mbit/sec–1 Gbit/sec range, once a link is established between the devices 52/12. Once the synchronization is complete, the devices 52/12 exchange a signal.

In an alternate embodiment of the present invention (FIG. 4), a system 10' also provides identification of a user and authorization for the user to interact with a processor 12. This system 10' comprises a visual display device 20. Integrally mounted with the display 20 are a first detector 30 and a second detector 32.

The first detector 30 is, as above, adapted to receive an electromagnetic signal within a predetermined wavelength range, such as a transponder reader. The first detector 30 is further adapted to transmit the electronic signal.

The second detector 32 is adapted to receive the electronic signal from the first detector 30 and to perform thereupon a visual scan of a user. The second detector 32 is further adapted to transmit in electronic form data representative of the visual scan to the processor 12. Such a visual scan may comprise, for example, a retinal scan, a facial scan, or a fingerprint scan, although these are not intended as limitations. The processor 12 has means 21 resident therein or accessible thereby for comparing the visual scan data with a database 22 of approved user visual scan data.

Upon a match being achieved by the comparing means **21**, a transmitter in electronic communication with the processor **12** transmits an approval code from the processor **12** to the visual display device **20**. The approval code is for permitting interaction between the user and the processor **12** via the visual display device **20** and to display a communication from the processor **12** to the user.

Exemplary applications include access to email or other messages at intranet or internet kiosks; access to a computer system; authorization by a security system to obtain information or obtain access to an area; authorization to record and complete a sale, such as at a restaurant or retail outlet; authorization to make reservations or register for a class; and access to an information system such as by a medical professional.

It may be appreciated by one skilled in the art that additional embodiments may be contemplated, including different types of transponders, readers, and peripheral devices, and alternative identification device designs.

In the foregoing description, certain terms have been used for brevity, clarity, and understanding, but no unnecessary limitations are to be implied therefrom beyond the requirements of the prior art, because such words are used for description purposes herein and are intended to be broadly construed. Moreover, the embodiments of the apparatus illustrated and described herein are by way of example, and the scope of the invention is not limited to the exact details of construction.

Having now described the invention, the construction, the operation and use of preferred embodiment thereof, and the advantageous new and useful results obtained thereby, the new and

useful constructions, and reasonable mechanical equivalents thereof obvious to those skilled in the art, are set forth in the appended claims.